



For more Information visit our website at [www.mpstor.com](http://www.mpstor.com)

## XD2U24-SBB FC/SAS/SATA RBOD

### High Performance and High Versatility Desktop RAID Subsystem

XD2U24-SBB-HC series FC/SAS-SAS/SATA RBOD is the next generation rack mounted RAID subsystem designed for high performance storage demands in the industry standard SBB format. With 12Gbps wide SAS bandwidth host and expansion interface supporting both SAS and SATA drives, XD2U24-SBB-HC quadruples the standard data transfer rate of a conventional SATA/SAS RAID subsystem. In additions, XD2U24-SBB-HC can be configured with dual 4G Fiber Channel host interface with 8Gbps bandwidth for maximum versatility. The XD2U24-HC supports dual controller configurations and is the highest capacity 2U system on the market with its unique dual disk drive carrier. The XD2U24-HC can support up to 48TB of RAID storage.

XD2U24-SBB-HC enables users to manage storage through the Xtreme Storage Manager, a user-friendly web-based Storage Management GUI that puts remote management and system administration at user's fingertips.

#### KEY FEATURES & BENEFITS

- Hardware RAID design, support RAID 0, 1, 10, 5, and 6
- Universal backplane supports the mix-match of SAS & SATA drives
- 12Gbps wide SAS host and expansion ports, with optional 8Gbps 4G FC host ports
- Cable-less backplane/controller design for maximum reliability
- Auto detect drive type and QOS label - Partial rebuild & spare rebuild caching
- Logical Volume Virtualized Storage with Instant Volume Availability, Online Volume Resize, Host Mapping & Masking and Simultaneous FC & SAS LV Exports
- Xtreme Storage Manager, a web-based management software with graphical user interface over Ethernet
- Event Notification through EMAIL/ SNMP
- SCSI Enclosure Services (SES) for drive, fan, power and system temperature monitoring



XD2U24 front view



XD2U24 back view

Supports 24 3.5" SAS/SATA drives in a 2U rack mount Format. Each shuttle supports dual disk drives




#### High Performance Desktop RAID Solution

The data bandwidth of XD2U24 is 1200MBps per SAS host connection, with optional 800MBps dual Fiber Channel Connection. The performance of the bus is achieved by combining four SAS channels with each supporting 3Gbps full duplex speed. Together with a high-speed SAS HBA or SAS RAID controller card in the host server, this storage enclosure can deliver an unprecedented performance.

#### Easy Maintenance and Management

XD series supports SES (SCSI Enclosure Service) for status monitoring and in-band firmware update. User can perform remote management through web-based Xtreme Storage Manager for system status monitoring.

# XD2U24-SBB FC/SAS/SATA RBOD



## SPECIFICATIONS

<b>Model Number</b>	XD-2U-SBBHC-0024R-B
Host Interface	1 x 12Gbps SAS wide port (Optional) 2 x 4Gbps Fiber Channel port
Expansion Interface	1 x 12Gbps SAS wide port
RAID Chipset	667 MHz RISC processor
Data Cache	1GB default
Drive Support	Hot-swappable 3.5-inch SAS & SATA drive, up to 15,000 rpm
No. of Drive Trays	24 3.5 " disks
Logical Volume	Instant Volume Availability, Online Volume Resize, Dynamic Mount/ Unmount Host LV, Auto Detect RAID Set Type / QOS
RAID Level	0, 1, 5, 6, 10
Max. RAID set per LV	5
Configurable RAID Stripe Size	64K, 128K, 256K
Other RAID Features	Auto Detect Drive Type, Global Spare, System Wide Drive Roaming, Configuration on Disk
OS Support	Microsoft Window Vista, 2000 Server, 2003 Server, Mac OS, RedHat Linux, SuSE Linux, Fedora
Storage Management Software	Extreme Storage Manager (Web-based GUI over Ethernet)
Event Notification Method	EMAIL
AC Input	100VAC ~ 240VAC 300W with PFC
DC Output	12V@16A, 5V@18A, 3.3V@16A
Operating Temperature	40 °F ~ 120 °F Non-condensing
Non-operating Temperature	41 °F ~ 140 °F Non-condensing
Dimension (H x W x D)	19 x 28 x 3.5
Weight	28 lbs
Emission & Safety	FCC / CE / UL
Quality	ISO 9001 / 140000
Warranty	Three years*

### Contact us:

European Sales at  
Tel: +353-21-4208959  
Email: [sales@mpstor.com](mailto:sales@mpstor.com)  
URL: [www.mpstor.com](http://www.mpstor.com)

©2009 MPSTOR LTD. All Rights Reserved  
MPSTOR and MPSTOR logo are MPSTOR  
trademarks. All other trademarks are the  
property of their respective companies.

PUB-00045-B 03/30/09 Product specifications subject to change without notice.